

3/14/2015

HID/CFL Fixtures

Mid-Size Wide Flood

PS / 150 watts | CF / 52 watts

Applications

Perfect for lighting building facades, displays, signs, or for general security lighting purposes

Features

- Die-cast housing with hinged door frame for easy relamping (lamp included)
- Textured bronze finish with tempered glass lens
- 1/2" adjustable knuckle
- UL listed for wet locations
- EPA = 0.75 sq. ft.; Max. fixture weight = 15 lbs.

**RAPID SHIP MODEL
AVAILABLE FOR NEXT DAY SHIPMENT**

- MSWF-150-PS-4T

Project:	
Catalog#:	
Approved by:	



ORDERING INFORMATION					
Catalog #	Watts	Volts †	Ballast	ANSI	Lamp Part #
MSWF-150-PS-4T	150 PSMH	4T	HX-HPF	M102	MH150/U/MED
MSWF-52-CF-MV	52 CF	MV	Electronic	-	(2) - CF26DT

ACCESSORIES (sold separately)	
Catalog #	Description
MSWVG	Wire guard with stainless steel construction
MSFGS	Black powder-coat finished glare shield that can be reverse mounted to use as a back cutoff
MSFVG	Clear polycarbonate vandal guard
FLGSTK	HID ground stake with position adjustable stabilizer, die-cast fitting that accepts 1/2" knuckle, and built in wiring compartment

DIMENSIONS

MOUNTING DETAIL

PHOTOMETRICS

150W PSMH @ 15' Mounting Height & aimed 30° Below Horizontal

footcandles

† 2T = 120, 277 volts (pre-wired to 277)
 MV = 120-277 Universal Input
 4T = 120, 208, 240, 277 volts (pre-wired to 277)
 5T = 120, 208, 240, 277, 480 volts (pre-wired to 277)
 120 = 120 volts
 480 = 480 volts
 Pre-wiring to any specific voltage is available upon request
 Specifications subject to change without notice.

